

ARENDSVILLE BOROUGH COUNCIL
P. O. Box 508
ARENDSVILLE, PA 17303
(717) 677-6009

SIMPLIFIED APPROACH STORMWATER INFORMATION

- The filing fee for consideration of a Stormwater Management Plan will be broken into categories based upon the type of Stormwater Plan required. The monies will be deposited with the Borough prior to the Borough's consideration of the Plan.
- Simplified Approach Administrative Fees: \$50 - \$75 depending on the Plan.
- Deposit for Consultant's Review/Inspection: \$150 - \$275 depending on the Plan. (Any unused portion of the deposit for reviews will be refunded to the applicant. If the review fees exceed the amount of the deposit, the applicant will reimburse the Borough for the increased fees.)
- Stormwater Worksheet A & B are required. Worksheet A is to include present impervious surface, proposed impervious surface, and total impervious surface upon completion of the project. Worksheet A will need to be notarized.
- A Sketch Plan or Minor Stormwater Site Plan (depending on the Plan) is required.
- All outstanding fees will need to be paid prior to the release of the signed Stormwater Management Plan or the issuance of Land Use Permits, Building Permits, or Use & Occupancy Permits.
- Fee for a copy of the Stormwater Management Ordinance is \$10 per copy. Single sheet copies are available for \$0.25 per sheet.
- Fee for a copy of the Complete Design Assistance Manual is \$10 per copy. Single sheet copies are available for \$0.25 per sheet.

COPY RECEIVED _____ DATE _____

Applicant's Signature

*\$50.00 Administrative Fee & possible consultant fees applicable based on the Plan Type. Fees will be due prior to issuance of Land Use Permit.

Arendtsville Borough Simplified Design Approach Worksheet A

Property Owner's Name _____
Applicant Name _____

Applicant / Owner Address _____
and phone number _____

Address of Property _____

Tax Map Parcel ID # _____
Parcel Size (approx) _____

A Sketch Plan must be included and show the following:

Total existing impervious area on the property _____
New impervious area proposed _____
Total impervious area on the property after _____
project completion _____

Are there any known existing drainage problems or the potential for the proposed project to create drainage problems? (if yes, please explain)

NOTARIZATION:

Acknowledgement – I declare that I am the property owner, or representative of the owner, and that the information provided is accurate to the best of my knowledge. I understand that stormwater may not adversely affect adjacent properties or be directed onto another property without written permission. I also understand that false information may result in a stop work order or revocation of permits. Municipal representatives are also granted access to the property for review and / or inspection of this project if necessary.

Applicant Signature _____ Date _____

Notary: _____ Date: _____

My Commission expires _____

To be completed by authorized municipal official

Type of Stormwater Management Required:

- Exempt from stormwater management plan preparation _____
(Worksheet A and Sketch Plan)
- Minor stormwater management site plan preparation _____
(Complete Worksheet B to determine necessary BMP's)
- Formal stormwater management plan preparation _____
(Consult a professional)

Determined by: _____ Date: _____

Arendtsville Borough Simplified Design Approach Worksheet B

Step 1: Determine the amount of impervious area created by the proposed projects. This includes any new surface area that inhibits the infiltration of stormwater into the ground. New stone and gravel areas are considered impervious. Existing impervious areas are not included in this calculation.

Table # 1

Surface	Length	x	Width =	Total Impervious Area (SF)
Buildings				
Buildings				
Driveways				
Parking Areas				
Patios/Walkways				
Decks				
Other				
			Total Proposed Impervious Area =	

Step 2: Determine the Disconnect Impervious Area (DIA). All or parts of proposed impervious surfaces may qualify as Disconnected Impervious Area if runoff is directed to a pervious area that allows for infiltration, filtration and increased time of concentration. The volume of stormwater that needs to be managed could be reduced through DIA. Prepare a Minor Stormwater Management Site Plan to determine DIA.

Determining Status of DIA

- a) Determine contributing area of the roof/driveway to each disconnected discharge. If it's 500 ft² or less (for a roof) or 1,000 ft² or less (for a driveway), continue to "b". If it's greater than these amounts, the area does not qualify as a DIA.
- b) Determine the length of down slope pervious flow path available for each disconnected discharge.
- c) Determine the % slope of the pervious flow path, % slope = (rise/ run) x 100. Must be 5% or less.
- d) See the table on the next page to determine the percentage of the area that can be treated as disconnected. If the available length of the flow path is equal to or greater than 75 ft, the discharge qualifies as entirely disconnected.

Partial Disconnections		
Length of Pervious Flow Path* (ft) Lots 10,000 ft ² and Under	Length of Pervious Flow Path* (ft) Lots >10,000 ft ²	DIA Credit Factor
0 – 7.9	0 – 14	1.0
8 – 15.9	15 – 29	0.8
16 – 22.9	30 – 44	0.6
23 – 29.9	45 – 59	0.4
30 – 34.9	60 – 74	0.2
35 or more	75 or more	0
*Pervious flow path must be at least 15 feet from any impervious surface and cannot include impervious surfaces.		

Using step 2 calculations calculated from the minor stormwater site plan, complete the table below. This will determine the impervious area that may be excluded from the area that needs to be managed through stormwater management BMP's. If total impervious area to be managed is zero, the area can be considered entirely disconnected and further calculations are not needed.

Table # 2

Surface	Area (SF)	x	DIA Credit =	Impervious Area to be Managed (SF)
Buildings				
Buildings				
Buildings				
Buildings				
Buildings				
Driveways				
Driveways				
Parking Areas				

***If total impervious surface area to be managed is greater than zero, continue to Step 3.**

Step 3: Calculate the volume of stormwater runoff created by proposed impervious surfaces.

$$\begin{array}{rclclcl}
 \text{Impervious Area (SF) to be} & & \times & 2.8\text{in}/12\text{in} = 0.233 & = & \text{Volume of Stormwater} \\
 \text{Managed (Sum from Table 2)} & & & \text{(from 24hr rainfall)} & & \text{to be Managed (CF)} \\
 & & \times & 0.233 & = &
 \end{array}$$

Step 4: Select BMP's and size according to the volume of stormwater that needs to be managed in Step 3.

Table # 3 - BMP Sizing Table*

BMP Type	Necessary Volume** (from Step 3 above)	Length	Width	Depth	Void Ratio	Volume ***
Infiltration Bed or Trench					0.4	
Infiltration Berm					1	
Rain Garden					0.4 in stone 1.0 above ground	
Rain Barrel or other usable storage		Use known volume of rain barrel, etc. 1 cubic foot is equal to 7.48 gallons.			1	
Other						

* Chart should only be used when a formal SWM Site Plan is not required.

** Should not include areas that were proven to be 100% disconnected